

INSTRUCTIONS TO CONNECT THE FRUCOSOL FREEZER MACHINE

STEPS TO FOLLOW

- THE MACHINE IS SENT IN ONE PALLET
- IT IS DISMOUNTED, THAT IS, THE MACHINE FOR ONE SIDE AND THE STAND WITH THE COOLING SYSTEM BY THE OTHER
- FIRST OF ALL, WE HAVE TO CONNECT THE COOLING SYSTEM TO THE MACHINE; TO DO THAT, WE HAVE MADE TWO CONNECTION BOXES, ONE FROM THE COOLER AND THE OTHER ONE FROM THE MACHINE.
- TO GET THE CONNECTORS OF THE MACHINE, YOU HAVE TO TAKE FROM THE UNDER SIDE OF THE MACHINE. AS THE MACHINE IS OPEN AT THE BOTTOM, YOU WILL BE ABLE TO GET IT EASILY.
- ONCE YOU HAVE IT, JUST CONNECT THE TWO CONNECTORS, ALWAYS WITH THE MACHINE DISCONNECTED FROM THE NET.
- TO FIX THE MACHINE TO THE CABINET, YOU HAVE TO UNSCREW THE 4 BLACK "LEGS" OF THE MACHINE AND SCREW IT TO THE STAND (IT IS MADE WITH 4 HOLES THAT COINCIDE WITH THE SCREWS OF THE MACHINE).
- ONCE YOU HAVE MADE ALL THESE THINGS, THE MACHINE IS READY TO BE USED. PAY ATTENTION TO THE FUNNEL, AS IT HAS TO BE PROPERLY INSTALLED TOGETHER WITH THE DEPOSIT FOR THE JUICE.
- THE COOLING SYSTEM IS SENT WITH A FIXED TEMPERATURE (THE BEST ONE FOR THE USE). HOWEVER, IT CAN BE REGULATED AS IT HAS A THERMOSTAT AT THE BOTTOM SIDE OF THE DEPOSIT.
- IF YOU HAVE ANY DOUBT DO NOT HESITATE IN CONTACTING US.