

## INSTRUCTIONS TO CONNECT THE SELF SERVICE

### STEPS TO FOLLOW

- THE MACHINE IS SENT IN ONE PALLET
- IT IS DISMOUNTED, THAT IS, THE MACHINE FOR ONE SIDE AND THE STAND BY THE OTHER
- TO FIX THE MACHINE TO THE CABINET, YOU HAVE TO UNSCREW THE 4 BLACK "LEGS" OF THE MACHINE AND SCREW IT TO THE STAND (IT IS MADE WITH 4 HOLES THAT COINCIDE WITH THE SCREWS OF THE MACHINE.
- ONCE YOU HAVE MADE THESE THINGS, THE MACHINE IS READY TO BE USED.
- THE MACHINE HAS TWO SWITCH BUTTONS, ONE FOR THE AUTOMATIC FEEDER SYSTEM, AND THE OTHER ONE FOR THE MACHINE. TO START TO WORK, YOU HAVE TO PRESS BOTH BUTTONS, BUT THE MACHINE WON'T WORK.
- IT WILL START TO WORK WHEN YOU PRESS THE FAUCET BACK TO THE END. WHEN YOU DO THAT, THE MACHINE WILL START TO WORK AUTOMATICALLY, AND IT WILL STOP WHEN THE FAUCET COMES TO THE INITIAL POSITION.
- FROM TIME TO TIME, YOU WILL HAVE TO EMPTY THE FUNNEL AND PIPES OF THE FAUCET. YOU WILL BE ABLE TO DO THAT JUST DISCONNECTING THE AUTOMATIC FEEDER SYSTEM (TO AVOID MORE ORANGES GET INTO THE MACHINE) AND PRESSING THE FAUCET.
- IF YOU HAVE ANY DOUBT DO NOT HESITATE IN CONTACTING US.